

TELEFUNKEN

VALVOLE: 1) WE 43 1) WE 33 1) WE 37
VALORI CONDENSATORI

| | | | |
|----|-----------|----|-----------|
| 15 | 50 pF | 52 | 5-30 pF |
| 18 | 5-30 pF | 53 | 14-18 pF |
| 22 | 25 pF | 54 | 1000 pF |
| 23 | 5-30 pF | 55 | 30000 ohm |
| 25 | 25-80 pF | 56 | 20000 pF |
| 26 | 5-30 pF | 57 | 2500 ohm |
| 27 | 25-80 pF | 58 | 20000 pF |
| 28 | 5-30 pF | 59 | 200 pF |
| 29 | 100000 pF | 62 | 200 pF |
| 30 | 1 M · ohm | 63 | 20000 pF |
| 31 | 25000 ohm | 64 | 200 ohm |
| 32 | 50 ohm | 65 | 5000 pF |
| 36 | 20000 pF | 66 | 50000 ohm |
| 37 | 50000 pF | 67 | 20000 pF |
| 38 | 200 ohm | 68 | 50000 ohm |
| 39 | 20000 ohm | 70 | 20000 pF |
| 40 | 100 pF | 71 | 200 pF |
| 51 | 25-60 pF | 74 | 200 pF |

779-783

1) WE 39 1) WE 38 1) WE 38 1) WE 53
E RESISTENZE

| | | | |
|----|--------------|---------|------------|
| 75 | 50 pF | 92 | 8 MF |
| 76 | 50 pF | 93 | 8000 ohm |
| 77 | 250 K · ohm. | 94 | 8 MF |
| 78 | 100 K · ohm | 95 | 8000 ohm |
| 79 | 100 pF | 96 | 1 M · ohm |
| 80 | 1 M · ohm | 97 | 20000 pF |
| 81 | 2 M · ohm | 98 | 20000 pF |
| 82 | 2 M · ohm | 99 | 300 pF |
| 83 | 2 M · ohm | 100 | 100000 ohm |
| 84 | 20 pF | 101 | 0,5 MF |
| 85 | 0,2 M · ohm | 102 | 50000 ohm |
| 86 | 20000 pF | 103 | 100000 pF |
| 87 | 40000 ohm | 105 | 10 MF |
| 88 | 50 ohm | 106 | 75 ohm |
| 89 | 10 MF | 107 | 5000 pF |
| 90 | 4000 ohm | 108 | 1300 pF |
| 91 | 200 ohm | 112-113 | 18 MF |